

# Confidea F-DM

## Confidea Flushmount Delegate Microphone Unit



### Description

The Confidea F-DM is Televic's microphone panel for basic discussion systems. Its small form factor, housed in an elegant casing, permits a minimalistic integration into any meeting room furniture.

Since the Confidea F-DM panel has no integrated speaker, it is intended for use at venues where a room sound system is already installed.

The panel has a screw-lock connector to fit a removable microphone (available in 30, 40 or 50 cm versions). The chairman version of this panel has additional controls (see Confidea F-CM 71.98.0515).

### Benefits

The Confidea F-DM is a sleek and discreet solution that is perfectly suited to conference rooms with an existing sound system. The unit is available in a variety of custom colors, sizes and finishes to blend in neatly in any environment.

The Confidea F-DM is backed by the Plixus® network and redundant cabling to ensure maximum reliability. Finally, its shielded microphone is immune to mobile phone interference.

### Features

- » Basic discussion function
- » Tactile microphone push button with integrated LED
- » Rounded corners for easy installation
- » Trademark natural Televic Sound
- » Available in custom colors, sizes, finishes

## Connectivity

- » Screw-lock microphone connector. Microphones sold separately.

<b>D-MIC30SL</b>	<b>71.98.0053</b>
<b>D-MIC40SL</b>	<b>71.98.0054</b>
<b>D-MIC50SL</b>	<b>71.98.0055</b>

- » Two RJ 45 connectors for loop through cabling
- » Plixus-powered

## Software

- » To fully configure, manage, and use the unit, Televic's CoCon management software is required. The following standard licenses are available:

<b>CoCon Discussion</b>	<b>71.98.1101</b>
<b>CoCon Signage</b>	<b>71.98.1102</b>

## Certifications

Region	Certification
Europe	CE

## Specifications

Mechanical	
Material	Steel
Color	Tiger coating Carbon 01
Size (mm)	155 (w) × 50 (h) × 85 (d)
Size packed (mm)	190 (w) × 85 (h) × 105 (d)
Weight	280g
Weight packed	360g
Electrical	
Voltage	48 VDC
Current consumption	3 W
Microphone Input	
Dynamic range	> 90 dB
Frequency response	20-20,000 Hz
THD @ nominal level	0.1%

# Technical Drawing

