



TS-904SL-AS

Microphone



We supply sound, not equipment
www.TOAcanda.com

TS-904SL-AS

Conference Microphone

The TS-904SL-AS Microphone is designed for exclusive use with the TOA conference systems. Ring type In-Use lamp located at the microphone head permits displaying the operation status of the conference units.

- Extended Gooseneck Length.
- Unidirectional
- Compatible with 600/700/800/900 Conference systems



Specifications

TS-904SL-AS

Type Directivity	Electret condenser microphone
Rated Impedance	Unidirectional 1.8 kΩ
Rated Sensitivity	-37 dB (1 kHz 0 dB = 1 V/Pa)
LED Indicator	Speech indicator (ring type)
Frequency Response	100 hz -13 KHz
Output Connector	Combined type of XLR-4-32
Operating Temperature	0 to 40 °C (32 to 104 °F)
Operating Humidity	90% RH or less (no condensation)
Finish	Gooseneck: Stainless steel, black Other: ABS resin, black
Length	720 mm (28.35")
Weight	130 g (0.29LB)
Applicable Unit (Option)	Chairman TS-681, TS-781, TS-801, TS-811, TS-901, TS-911 Delegate unit: TS-682, TS-782, TS-802, TS-812, TS-902, TS-912

TOA Canada Corporation

Tel: 1-800-263-7369

Fax: 1-800-463-3569

sales@toacanada.com • www.TOAcanda.com

