ONKYO



Speakers That Add Dynamism to Your Music and Movies

Onkyo crafted the 4800-series speakers as a failsafe way to bring energy and full-spectrum power to your home entertainment. The series includes a pair of stylish floor-standing front speakers and a compact center/surround package, sold separately. Twin 16 cm woofers provide the SKF-4800 front speakers with the heft to handle dynamic classical scores and towering rock anthems with equal aplomb. Even at high volume levels, your music will sound full and natural, with stunning detail across the audio spectrum. To create an atmospheric surround-sound effect—especially for movie and game soundtracks—the front speakers can be partnered with the SKS-4800 center/surround speakers. Precision-matched, for a truly immersive audio experience.

SKF-4800

- 16 cm Cone Woofer x 2
- 2.5 cm Soft-Dome Tweeter
- Max. Input Power: 130 W
- Banana Plug-Compatible Speaker Posts
 Max. Input Power: 130 W
- Woofer Equalizer Enables Fast and
- Accurate Response
- MDF Stabilizer to Prevent Vibration
- Décor-Enhancing Natural Finish
- Stylish Floor-Standing Design

SKS-4800

- 2-Way Bass Reflex Front Speakers Center/Surround Speaker Package SKC-4800 2-Way Bass Reflex Center Speaker
 - 8 cm Cone Woofer x 2
 - 2.5 cm Balanced-Dome Tweeter

 - Magnetically Shielded
 - SKR-4800 Full-Range Acoustic Suspension
 - Surround Speakers 8 cm Cone
 - Max. Input Power: 60 W
 - Note: All speakers feature an impedance of 6 Ω . Center and surround speakers are wall-mountable

SPECIFICATIONS

Speaker Type		Nominal Impedance	
Front (SKF-4800)		Front/Center/Surround	6 \$2
Center (SKC-4800)		General	
Surround (SKR-4800)	Full-range, acoustic suspension	Dimensions (W \times H \times D)	
Drivers		Front	295 × 1024 × 305 mm
Front	16 cm cone woofer x 2	Center	372 x 125 x 110 mm
	2.5 cm soft-dome tweeter	Surround	117 x 180 x 100 mm
Center	8 cm cone woofer x 2		
	2.5 cm balanced-dome tweeter	Weight	12.01
Surround	8 cm cone	Front	13.0 kg
Frequency Response		Center	2.3 kg
Front	55 Hz–35 kHz	Surround	0.9 kg
Center	65 Hz–50 kHz	CARTON	
Surround	80 Hz–18 kHz		
Output Sound Pressure Level		SKF-4800	1140
Front	86 dB/W/m	Dimensions (W x H x D)	1140 x 372 x 700 mm
Center	86 dB/W/m	Weight	33.0 kg
Surround	81 dB/W/m	SKS-4800	
Max. Input Power		Dimensions (W x H x D)	463 x 274 x 321 mm
Front/Center	130 W		5.5 kg
Surround	60 W	9	

Due to a policy of continuous product improvement, Onkyo reserves the right to change specifications and appearance without notice



Onkyo Sound & Vision Corporation 2-1 Nisshin-cho, Neyagawa-shi, Osaka 572-8540, JAPAN http://www.onkyo.com/ Onkyo China Limited Unit 1033, 1045, Star House, No. 3, Salisbury Road, Tsim Sha Tsui, Kowloon, Hong Kong, CHINA Tei: 852-2429-3118 Fax: 852-2428-9039 http://www.onkyochina.com/ Onkyo U.S.A. Corporation 18 Park Way, Upper Sadel River, NJ, 07458, U.S.A. Tei: 1-201-785-2600 or 800-229-1687 (Tol Iree) Fax: 1-201-785-2650 http://www.eonkyousa.com/ Onkyo Eucope Electronics GmbH Liegnitzerstasse 6, 82194 Groberzell, GERMANY Tei: 49-8142-4401-0 Fax: 49-8142-4401-555 http://www.eonkyo.com/