



ACS-1500 Series

PROFESSIONAL ACTIVE COLUMN SPEAKER SYSTEM



ACS-1500 Series

ACS-1500 Series Professional Active Column Speaker System which can cover the usage area from small to large designed for hi-end professional sound performance specifically for frequency response up to 40Hz ~ 18KHz \pm 3dB, Power maximum 1800 Watts Amplifier Class D with DSP processor 5 Preset for best performance. And can stream wireless music via Bluetooth support ideal life sound concert, event, shopping mall, meeting room - training, fitness, restaurant, hotel banquet room.

This series includes ACS-1500S (Subwoofer), ACS-1500C (Column Speaker)

Feature

- Subwoofer Component: 15", 3" voice coil
- Satellite Components: 4" X 8 Full Range Speaker
- Dispersion Angle (H x V): 80 x 20 Degree.
- Frequency response: 40Hz ~ 18KHz
- Max. SPL / (Peak): 125dB/134dB
- Power RMS: 900W / 1800W (MAX)
- Built-in Class D Amplifier
- Built-In DSP Processor Mode: DEFAULT, MUSIC, DANCE, SPEECH, POP
- Built-in Media player: Wireless stereo audio streaming Bluetooth.
- Operating voltage AC 220 - 240V, 50/60Hz

Specifications

Model	ACS-1500S (Subwoofer)	ACS-1500C (Column)
Transducer	Subwoofer Components : 15", 3" voice coil	Satellite Components : 4" X 8 Full Range Speaker
Frequency Response	40Hz ~ 180Hz \pm 3dB	110Hz ~ 18kHz \pm 3dB
Rated Power	600W / 1200W (MAX)	300W / 600W (MAX)
Amplifier	Class D	
Sensitivity	95dB 1m/1W	96dB 1m/1W
Maximum SPL	125dB/134dB (Peak)	125dB/134dB (PEAK)
Nominal Impedance	4 Ω	4 Ω
Built-in DSP Processor	DEFAULT, MUSIC, DANCE, SPEECH, POP	
Audio Streaming Wireless	Bluetooth Version 4.0	
Dispersion Angle (H x V)		80° X 20°
Connection	Line Input: XLR or 1/4" Jack, Line Output: XLR	SPEAKON
Operating voltage	AC 220~240V, 50/60Hz	
Dimensions (W x H x D)	430 x 520 x 570mm	135 x 135 x 980mm
Net Weight	27	11