







Selecting a powered speaker solution should never be a compromise. The Cerwin Vega CV Series speaker line delivers best in class design whether your audio needs are small, medium or large coverage applications. The CVX line of four powered speakers (single 10" and 15" tops, with 18" and 21" subwoofers) are true road warriors. With up to 1500 watts of clean power (2000 watts for Subwoofers), wide dispersion, fully defined bass, and smooth highs, the CVX speakers deliver a big, clear sound that blankets an audience evenly. All this is wrapped in a surprisingly portable enclosure for a modern, professional appeal that can withstand years of use. For touring, ballrooms, medium to larger clubs, outdoor venues, houses of worship, rentals and staging applications, the CVX line—fueled by Cerwin Vega's 65 years of professional live sound solutions—delivers power to spare, with accurate, sonic precision.

KEY BENEFITS

- 1500 Watts Class D Power with 2000 Watts for Subwoofers
- 3 Channel Mixer with 2 Combo XLR/TRS Inputs,
 1 TS Stereo Input & 3 XLR Outputs
- Main/Monitor and Live/Playback EQ Modes
- Front Clip Indicator
- Lightweight, durable top cabinets with Tour Shield™ subwoofer finish
- · Cardioid Mode



01/1/ 40*







	CVX-10*	CVX-15*	CVX-18s*	CVX-21s*
Power Rating	1500	1500	2000	2000
Amplifier Class	D	D	D	D
Frequency Response (+/- 3dB)	62Hz - 20kHz	54Hz - 22kHz	38Hz - 146Hz	35Hz - 154Hz
Frequency Range (-10db)	54Hz - 22kHz	42Hz - 24kHz	34Hz - 175Hz	31Hz - 194Hz
Max SPL	134	134	135	135
HF Driver	1"	1.4"	N/A	N/A
LF Driver	10"	15"	18"	21"
Dispersion	90° x 60°	90° x 60°	N/A	N/A
Input/Output	(2) Combo XLR/TRS Inputs (1) TS Pair Input (3) XLR Outputs	(2) Combo XLR/TRS Inputs (1) TS Pair Input (3) XLR Outputs	(2) Combo XLR/TRS Inputs N/A (3) XLR Outputs	(2) Combo XLR/TRS Inputs N/A (3) XLR Outputs
Switches	Main/Monitor Mode Live/Playback EQ High Pass Filter Front Clip Indicator	Main/Monitor Mode Live/Playback EQ High Pass Filter Front Clip Indicator	Polarity Cardioid Mode Crossover Frequency Front Clip Indicator	Polarity Cardioid Mode Crossover Frequency Front Clip Indicator
Enclosure	Polymer	Polymer	18mm Birch Plywood	18mm Birch Plywood
Finish	Standard	Standard	TourShield	TourShield
Dimensions (h x w x d)	541mm x 312mm x 303mm	698mm x 434mm x 345mm	621mm x 535mm x 649mm	713mm x 600mm x 787mm
Weight (lbs)	38.76	55.44	95.1	118.2

