



SOUNDVISION KBD 2160Di New generation network (IP Based) PTZ camera controller 10.1-inch touch screen simple UI design. Support H.265 1 CH 4K@30fps ; H.264 1 CH 1080P@60fp ; 4 CH 720P@30fps decoding. Real-time preview when the keyboard touch screen opened, And the image will come to the external display through the HDMI Interface.

EXAMPLE CONNECTION DIAGRAM



FEATURES

- 10.1-inch touch screen. Resolution 1280*800
- Support ONVIF & VISCA OVER IP protocol.
- Support network access to the full range of our PTZ Camera.
- RJ45, RS422, RS232 control interfaces.
- Adopt H.265 / H.264 / decoding, maximum 4 screen segmentation viewing images on the touch screen or putting images on the display via HDMI.
- Support the network access to the full range of our PTZ Camera.
- Adopt high-quality variable speed 4D joystick control.
- Support Android 6.0 operating system.
- Function supports up to 1024 devices to add / PTZ Control / Preset / Patrol and track setting and recall.



SPECIFICATIONS

Port	Network: RJ45, Serial Port: RS485, RS232, 2*HDMI 1.4, USB2.0
Protocol	ONVIF, ONVIF2.4, VISCA OVER IP
Interface	RS485, RS232, RJ45
Joystick	4D (up, down, left, right, zoom+, zoom-)
Display	IPS 10.1 inch touchscreen, Resolution 1280*800 Support HDMI 4K@30fps
Decoding	H264/H265 , H264 1x1080p@60fps , H264 4x720p@30fps , H265 1x4k@30fps
Prompt tone	ON/OFF
Power Supply	DC12V – 2A ±10%
Power Consumption	<15W
Standby current	<100mA
Mean time between failures	>30000
Working Temperature	-10°C ~ 40°C
Storage Temperature	-40°C ~ 60°C
Dimensions (WxLxH)	390 * 240 * 130 mm
Weight	1580g