



LA212

Applications

- Touring performance
- Stadium
- Theatre

Feature





- Large-scale, tri-amp, three-way line array system
- MF & HF parts is coaxial structure to optimise acoustic image
- Neodymium high-sensitivity driver, maximum headroom

Technical specification

- **FREQUENCY RESPONSE:** 50 Hz – 16 kHz (± 3 dB) / 40 Hz – 18 kHz (-10 dB)
- **NOMINAL COVERAGE^(@1m):** 100°(H) adjustable
- **SENSITIVITY(@1w/1m):** HF:113 dB SPL / MF:105 dB SPL / LF:100 dB SPL
- **POWER RATING(AES):** HF/MF/LF:160W/350W/800W
- **NOMINAL IMPEDANCE:** HF/MF/LF:16/16/12 ohm
- **MAXIMUM SPL:** HF:141 dB peak / MF:136dB peak / LF:135 dB peak
- **DRIVERS:** LF 2 x 12" (75mm Voice coil) woofer
MF 1 x 10" (65mm voice coil) mid range
HF 2 x 3" compression driver

Physical data


- **DIMENSIONS(HxWxD):** 367 x 1000 x 550mm / 14"x39"x22"
- **WEIGHT:** 63 kg / 139 lbs
- **CONNECTORS:** 2 x NL8 connectors
- **SPEAKER CABLES:** 1+1-...LF, 2+2-...MF, 3+3-...HF, 4+4-...N/C
- **MATERIALS:** 18mm, 24mm Baltic birch plywood
- **FINISH:** Black Polyurea paintings
- **GRILLE:** Black epoxy mesh grille with acoustically reticulated cloth
- **RIGGING:** 0, 1, 2, 3, 4, 5, 6, 7.5 degree adjustable



Front



Top



Side