

MA Series Switching Power Amplifier



2ch Professional Amplifier

MA2400S

Output power	
8Ω Stereo power	2×2400W
4Ω Stereo power	2×4000W
8Ω Bridged Mono power	1×8000W
4Ω Bridged Mono power	1×12000W



4ch Professional Amplifier

MA1300Q

Output power	
8Ω Stereo power	4×1300W
4Ω Stereo power	4×2200W
2Ω Stereo power	4×2400W
8Ω Bridged Mono power	2×4400W
4Ω Bridged Mono power	2×4800W

Technical Specification

Frequency response	20 Hz–25 kHz ± 0.5 dB
THD+N (Rated power,4Ω / kHz)%	0.1%
Signal noise ratio(dB)	98 dB
Optional gain	23,26,29,32,35,38,41,44 dB
Connection	
Input connectors (per.ch)	3–pin XLR,electronically balanced
Input impedance	20 kΩ Balanced / 10 kΩ Unbalanced
Output connectors	Speakon Connectors (Neutrik)
Power	
Power requirement	200–240V ~ (50 Hz–60 Hz)
Minimun requirement	180–260V ~ 50–60 Hz

Dimensions and Weight

Dimensions	483×377×88mm / 19"x15"x3"
Weight	13kg / 29 lbs