


VL audio S02N40 Speaker cable

Item	2*4.0mm2 Speaker cable	Spec	Φ 11.2mm(226/0.15BC*4.2mm)*2C
Conductor	Size	NO/mm	226/0.15BC
	Twist pitch(DIR)	mm	/
Insulation	Material	/	75P PVC
	Color	/	Red/Black
	Ave.thick	mm	0.97
	Min. thick	mm	0.92
	OD	mm	4.2±0.05
Filler	Material	mm	/
	OD	mm	/
Twisting	Twist	mm	/
	Total twist OD	mm	/
Shielding	Overlapping	mm	/
	Spiral	/	/
Outer jacket	Material	/	Environmental PVC
	Color	/	70P High flexible (MATTE) Black
	Ave.thick	mm	1.4-3.5
	Min. thick	mm	1.3-3.4
	OD	mm	Φ 11.2 ± 0.15mm
Electrical Data	Conductor-Conductor capacitance	PF/Km	<236.7
	Conductor-Shielding capacitance	PF/Km	/
	Conductor resistance (20℃)	Ω /Km	4.3
Marking			V-LINE S02N40 2*4.0mm2 PROFESSIONAL HIGH QUALITY SPEAKER CABLE BY VLAUDIO
Packaging		/	100M/ROLL
<p>Profile:</p> <div style="display: flex; align-items: center; justify-content: center;">  <div style="margin-left: 20px;"> <p>Conductor: 226/0.15BC</p> <p>Insulation: OD4.2 ± 0.05</p> <p>Outer jacket: Φ 11.2 ± 0.15</p> </div> </div>			