

V-BOX MARK-II

MONO PASSIVE DIRECT BOX

DESCRIPTIONS

The V-Box Mark-II Mono Passive Direct Box Is a high performance passive direct box for live concert touring and professional studio recording applications, featuring a VL transformer for exceptional audio performance.

FEATURE

- Stereo passive direct box designed for active instruments.
- Eliminates hum and buzz from ground loops.
- VL Transformers provide exceptionally linear response.

SPECIFICATIONS

Audio circuit type	Passive, Transformer based
Transformer	VL Transformer
Number of Channels	Mono
Frequency response	20Hz-20kHz
Dynamic range	135dB
Total harmonic distortion	0.002% @1k, +4dBu
Phase deviation	-1.45° @20Hz, -0.5° @100Hz
Input impedance	140kΩ Unbalanced
Output impedance	600Ω Balanced
Maximum input	+21dBu @20Hz - 20kHz (With Pad)

FEATURES

Ground lift	Yes
Input connectors	2 TS 1/4" (1 Thru)
Output connectors	2 XLR Male outputs

GENERAL



Conditions	For use in dry locations only
Warranty	Life time

SIZE

Height	48mm
Width	69mm
Depth	97mm
Weight	0.25kg

SHIPPING INFORMATIONS

Package height	52mm
Package width	92mm
Package depth	122mm
Package weight	0.35kg



V-BOX MARK-II : MONO PASSIVE GRAPHS

