



zoom

Certified

Compatible with ClickShare

BARCO





## Camera

- 4K optics lens, 120° FOV, up to 4X zoom
- · Sony 4K sensor: ultra-crystal-clear image in any lighting
- Frame rates: (16:9) 4K 30fps; 1920 x 1080, 1600 x 900, 1280 x 720, 960 x 540, 848 x 480, 800 x 448, 640 x 360, at 60, 30, 15fps; (4:3) 1280 x 960, 800 x 600, 640 x 480 at 60, 30, 15fps
- · Adjustable audio fence: freedom to define your meeting area
- Intelligent fill light: Automatically adjust lighting level to make you look energetic in virtual meetings in a dim environment\*
- SmartFrame: automatic FOV adjustment (auto focus)to fit all participants
- SmartSpeaker: Voice triggered tracking people or specific preset areas.
- True WDR up to 120db: 3D noise-reduction and superb backlight compensation optimize lighting in high-contrast conditions.
- Mirror, flip, AE, white balance: auto/manual override via PTZApp2
- Minimum focus distance: 60 cm
- People-counting API: enterprises and third-party software providers can obtain people-counting data for better understanding of meeting-space usage
- 10 camera presets (through remote control and IP web page)
  \*The best lighting distance is for people sitting within 1meter far from the camera

### **Audio**

- Beamforming microphone array: 5 microphones, 4 m pickup range
- · Echo cancellation and background noise suppression
- Supports expansion microphone
- 6Wx1 speaker with professional bass port tuned for communication
- 180Hz 20kHz Speaker frequency response
- Output volume: 94dB SPL +/-2dB at 0.5 meter

## Connectivity

- · 12V/2A power adapter
- · Mini-B for expansion microphone connection
- USB Type-B 3.1 connector, backward compatible with USB 2.0
- RJ45 port for Ethernet
- USB 2.0 Type-A for wireless connection\*

\*Optional wireless dongle is required to connect with mobile phone

## Video Format

- YUV, YUY2, MJPEG
- Network video compression format: H.264
- Network protocols: RTSP, RTMP\*

\*When USB streaming is in use, RTSP and RTMP are not available.

### USB

- 3.1 Gen 1, backward compatible with USB 2.0
- UVC 1.1 (USB video), UAC 1.0 (USB audio)

## Control

- IR remote control
- WebUI: IP access via Chrome browser (Chrome 76.x or later; Internet Explorer not supported)
- UVC/UVA plug-and-play
- PTZApp 2

### Mount

- Screen mount kit
- Camera wall-mount bracket

## **System Requirement**

- Windows® 7/10
- MacOS X 10.7 or later
- Google Chromebook™ version 29.0.1547.70

## **Hardware Specs**

- 3.2 GHz Intel® Core™ i5-4460 processor
- 4 GB RAM or more
- USB 3.1 port, backward compatible with USB 2.0

## **Power Supply**

- AC 100V-240V, 50/60 Hz
- Consumption: 12V/2A

## Free Applications for Meeting Collaboration (Free Apps support on Windows® and Mac® computers)

#### EZManager 2: Camera Central Management Software

 Remotely group FW/SW upgrades, control the camera, and manage settings

#### PTZApp 2: Camera Setting Software

- View live video, people counting number, meeting interval information
- Enable Skype for Business far-end control
- · Upgrade firmware automatically or manually
- Control the camera
- · Set parameters and adjust the camera image
- Diagnose operating status
- EZLive: Broadcasting Software
- Enjoy multi-camera real-time streaming, annotating, image capturing, and video recording

### **Environmental Data**

- Operation temperature: 0 ~ 40°C
- Operation humidity: 20% ~ 80%
- Storage temperature: -20 ~ 60°C
- Storage humidity: 20% ~ 80%

### **Dimensions**

- Package dimensions: 406(L)x146(W)x189(H) mm
- Package weight: 2.358 kg
- Camera: 350(L) x 65(H) x 75(D) mm/0.922 kg
- Remote control: 149.72 x 42.3 x 19.29 mm/50g

## **Package Contents**

- VB130 unit
- Power cable 10 ft (3 m)
- USB 2.0 Type-B to Type-A Cable 15 ft (5 m)
- $\cdot\,$  QR code card
- Screen mount or wall mount\*
- Remote control
- Tripod screw

\*Availability varies based on location. Please check with your local agent for details.

## **Optional Accessories**

- Wall mount and mounting screws
- Screen mount kit
- BT Dongle
- 10m/20m expansion microphone
- 10m/20m/30m USB 3.1 extension cable
- USB 3.1 GEN1 Type-B to Type-A cable, 3 m

### Warranty

- Camera: 3 years
- · Accessories: 1 year

## **Compatible Applications**

Microsoft® Teams, Skype for Business, Skype, Zoom, Google Meet<sup>™</sup>, Intel® Unite<sup>™</sup>, RingCentral, BlueJeans, V-Cube, LiveOn, CyberLink U Meeting®, TrueConf, Adobe® Connect, Cisco WebEx®, Fuze, GoToMeeting<sup>™</sup>, Microsoft® Lync<sup>™</sup>, Vidyo, vMix, WebRTC, Wirecast, XSplit

\*For 4K UHD support, please check system/hardware requirements with your software application provider.

\*\*Specifications may vary depending on countries and are subject to change without notice.

# **Product Overview**



## Angle-adjustable screen mount







©2021 AVer Information Inc. All rights reserved. All brand names and logos are trademarks of their respective companies.