

MVX2U DIGITAL AUDIO INTERFACE

XLR-TO-USB ADAPTER WITH HEADPHONE OUTPUT

OVERVIEW

The MVX2U Digital Audio Interface is a powerful, single-channel XLR-to-USB adapter that allows you to connect any XLR microphone to a computer for effortless recording and streaming. With configurable DSP features and full access to ShurePlus MOTIV Desktop App, the compact interface is future-proofed via online firmware updates. Providing up to 60dB of clean gain, the XLR-to-USB adapter has enough power to bring your favorite dynamic microphone, such as the legendary SM7B, to life. It also offers up to 48v of phantom power for connecting a condenser microphone to your computer. Portable, sleek and rugged, the MVX2U can be plugged straight onto an XLR microphone or used in-line with an XLR cable, depending on your setup.

FEATURES

- Make your favorite dynamic or condenser XLR microphone ready for podcasting or livestreaming with the MVX2U. The XLR-to-USB adapter enables digital recording and streaming right out of the box with Auto Level Mode and phantom power already switched on.
- Upgrade your XLR microphone with configurable onboard DSP via the ShurePlus MOTIV Desktop App.
- A built-in 3.5mm headphone jack with zero-latency monitoring ensures you'll get the desired audio output every time.
- Supplies 48v of phantom power for condenser microphones.
- Provides clean gain of up to 60dB that is sufficient to amplify signals for dynamic microphones such as SM7B. CPortable form factor with a sleek yet robust build can be plugged straight onto an XLR microphone or used in-line with an XLR cable depending on your desired setup.
- Compatible with both Mac and Windows, connect your XLR microphone directly to your computer with the included 1m USB-C to USB-C cable.







MVX2U Digital Audio Interface

SHUREPLUS MOTIV DESKTOP APP SOFTWARE FEATURES

The free app unlocks the following features for any XLR microphone using the MVX2U: below features are available made accessible for XLR microphones with MVX2U-



SHUREPLUS MOTIV™ DESKTOP APP

Supports MVX2U with any XLR microphones

AUTO LEVEL MODE	 Set your distance Near or Far from the microphone, and let MVX2U automatically adjust your gain level in real-time with intelligent onboard DSP for consistent audio output. Customize your vocal tone by selecting between a Dark, Natural or Bright sound signature.
MANUAL MODE	 Get full control of your mic output with configurable DSP features, such as Gain, Limiter, Compressor, EQ and more. Save your own presets for quick future access.
MONITOR MIX	 Set your preferred blend of monitoring and playback via the built-in headphone jack.
FIRMWARE UPDATES	 Firmware update ensure your interface will always have the latest features from Shure.



MVX2U DIGITAL AUDIO INTERFACE

XLR-TO-USB ADAPTER WITH HEADPHONE OUTPUT

SPECIFICATIONS

Input	XLR
Input impedance	5.8kΩ
Bit Depth	16-bit/24-bit
Sampling Rate	48kHz
Frequency Response	20Hz to 20,000Hz
Adjustable Gain Range	0 to +60dB
Maximum Input Level	7dBV
Power Requirements	Powered through USB-C
Phantom Power	+48VDC
Digital Noise Floor (20 Hz to 20 kHz, A-weighted)	-117dBFS
LED Indicator (Tricolor)	Green = Ready Amber = Error Red = Mute
Housing	All Metal
Net Weight	100 g (3.5 Oz.)
Dimension	44 x 140 x 158mm H x W x D
Headphone Output	3.5 mm (1/8 inch) 20 mW @ 32Ω
Cable	1M USB-C to USB-C cable

SYSTEM REQUIREMENTS

USB	USB 2.0
RAM	64MB RAM (minimum)
Operating System	MacOS 10.15 to 13 64 bit Minimum 2 GB of RAM Minimum 500 MB of hard disk space Windows 10 64 bit Minimum 2 GB of RAM Minimum 500 MB of hard disk space

AVAILABLE SKUS

MVX2U MOTIV XLR to USB Adapter

ACCESSORIES AND REPLACEMENT PARTS

95D52640 1M USB-C to USB-C cable



MVX2U What's in the box