



Technical Specifications



MONITOR SPEAKERS 1C

Ultra-Compact Monitor Speakers





MONITOR SPEAKERS 1C

Ultra-Compact Monitor Speakers

- Multi-purpose 2-way studio monitors ideally suited for fixed installation, multimedia, home recording studio, audio/video production and surround-sound systems
- Ultra-linear frequency range from 60 Hz to 23 kHz
- High power handling capability (100 W / IEC268-5) produces full-range output with extremely low distortion
- Phase-optimized and high-precision crossover for absolute phase linearity
- Auto overload protection prevents tweeter damage and resets automatically
- Powerful 5 ½" woofer with extremely light-weight cellulose cone and high-resolution ½" tweeter
- Solid protective grille and exceptionally rugged construction for long life and durability
- Conceived and designed by BEHRINGER Germany

Specifications

Clip terminal
< 4 mm
25 W RMS, 100 W Peak
4Ω
60 Hz to 23 kHz (-10 dB)
86 dB*W/m (program, bandwidth 100-5000 Hz on axis, full space)
112 dB @ 1m (on axis, half space)
1⁄2"
51/2"
5000 Hz

BEHRINGER is constantly striving to maintain the highest professional standards. As a result of these efforts, modifications may be made from time to time to existing products without prior notice. Specifications and appearance may differ from those listed or illustrated.