



M-89D DELEGATE

Specification

CON-999

Conference System whit video tracking

Main power supply	AC110V-220V/50Hz
Frequency response	20Hz-20kHz
Signal to noise ratio	>96dBA
Total harmonic distortion	<0.05%
Microphone Unit Interface	Din-8 socket interface x 2, RJ45 cable interface x 4
Central Connection	232 serial port x1
Camera interface	RS-232 small serial portx1
Camera interface	RS-422 serial portx1
HDMI video matrix interface	DB9/9 needles
Audio input	RCA (Lotus receptacle) x1
Audio output	RCA (Lotus receptacle) x1 XLR Canon socketx1
External Dimension	(L×W×H) 483×323×90mm
Color	Grayish black
Installation mode	19-inch Standard Cabinet

M-89C Chairman

M-89D Delegate

Operating Voltage	DC24V(Supplied by the mainframe)
Input, output	8P-DIN T line, Super Six network lines
Inputting	Heart-shaped directed electret
Sensitivity	-46 dBV/Pa
Frequency response	20Hz-20KHz
Input impedance	2 kΩ
Directivity 0°/180°	> 20 dB (1 kHz)
Equivalent noise	20 dBA (SPL)
Microphone maximum level	125 dB (THD<3%)
Signal to noise ratio	>80dB
Channel Crosstalk	>80dB
Total harmonic distortion	<0.05%
Display screen	128x32 PMOLCD
External dimensions do not include microphone	Poles 88×128×52mm
Weight	1.0kg
Color	Gray and black
Installation mode	Desktop style

