



DEFINITIVE TECHNOLOGY



## Dymension Outdoor BL Series All-Weather Bollard Speakers

Dymension Outdoor BL-550 and BL-650 bollard speakers deliver powerful sound in space-efficient designs. Timbre matched and featuring rigid, mineral-filled enclosures, these IP56-rated speakers seamlessly integrate with Dymension speakers in residential and light commercial settings.

### KEY BENEFITS

#### Impactful sound for outdoor spaces

Sleek, low-profile BL Series speakers deliver dynamic, balanced sound, courtesy of their mineral-filled woofers, premium tweeters, and built-in passive bass radiators.

#### Uncompromised outdoor sound

Dymension Outdoor speakers leverage Definitive Technology's innovative acoustic technologies to deliver clear, consistent sound in any outdoor space.

#### All-weather protection

Housed in rugged, durable enclosures, IP56-rated BL Series bollard speakers withstand harsh conditions while blending into their environment.

#### Fast, easy residential and commercial installs

BL Series bollard speakers provide 8Ω/70V/100V multitap settings for flexibility in distributed systems.

### PRODUCT FEATURES

- Rigid, well-damped 1" Dymension Series aluminum oxide dome tweeter delivers crisp, clear highs
- Mineral-filled woofer reproduces rich, clear sound that fills outdoor spaces
- Large passive bass radiator delivers impactful lows and contributes to dynamic, balanced overall sound
- IP56-rated design withstands rain, snow, and dirt to deliver premium sound in any weather
- Mounting holes and included ground spikes enable hardscape or softscape mounting
- Timbre-matched for seamless sound alongside Dymension speakers
- Silicone-sealed connections
- Sold as singles

## Dymension Outdoor BL Series All-Weather Bollard Speakers

SPECIFICATIONS		
	BL-550	BL-650
Mounting	Deck screws or ground spike	Deck screws or ground spike
IP Rating	IP56	IP56
Technical Features	Rigid, mineral-filled enclosure	Rigid, mineral-filled enclosure
Input	Jacketed single cable pigtail Multitap settings for direct-in, 70V & 100V use	Jacketed single cable pigtail Multitap settings for direct-in, 70V & 100V use
Drivers	1 in aluminum oxide dome tweeter 5.25 in mineral filled woofer	1 in aluminum oxide dome tweeter 6.5 in mineral filled woofer
Pressure Coupled Bass Radiator	5" × 8"	5.5" × 10"
Frequency Response	84 Hz–24 kHz (-3 dB) 55 Hz–32 kHz (-10 dB)	68 Hz–24 kHz (-3 dB) 44 Hz–32 kHz (-10 dB)
Sensitivity	86 dB (2.83V/1m)	87 dB (2.83V/1m)
Nominal Impedance	4Ω (8Ω compatible)	4Ω (8Ω compatible)
Recommended Amplifier Power	20-120W	20-150W
Available Colors	Brown	Brown
Warranty	5 years	5 years
Dimensions	Width: 10.6 in / 270mm Depth: 9.8 in / 248mm Height: 17.1 in / 435mm	Width: 11.9 in / 302mm Depth: 10.7 in / 272mm Height: 20.1 in / 510mm
Product Weight	8.6 lb / 3.9 kg	10.8 lb / 4.9 kg
Shipping Weight	13.2 lb / 6.0 kg	16.5 lb / 7.5 kg

