

Professional Series

Key Features:

- ▶ 10" Differential Drive® woofer for high-power capacity and very lightweight
- ▶ 1.5" annular polymer diaphragm compression driver
- ▶ Enclosure constructed of 15 mm plywood with rugged durable painting
- ▶ 80° x 70° coverage pattern for even and smooth response on and off axis
- ▶ Attractive 16 gauge protective screen backed steel grille
- ▶ Precision engineered crossover for optimal power response and performance in the vocal midrange region
- ▶ Single position pole socket for applications requiring pole mounting
- ▶ SonicGuard™ protects high frequency driver from excess power without interrupting the performance.
- ▶ Rotatable JBL ENTERTAINMENT logo for easy coherence to your application

Applications:

- ▶ Karaoke sound reinforcement
- ▶ Bar and club live or pre-recorded sound reinforcement
- ▶ High-performance satellite speaker for use with subwoofers

The KP6010 is a premium high-output lightweight full-range loudspeaker.

The KP6010 uses a JBL 261H 254 mm (10 in) Differential Drive® woofer and a 2408H-1 37.5 mm (1.5 in) annular polymer diaphragm, neodymium compression driver for 300 watts power capacity. 80° x 70° coverage pattern provides smooth, even coverage whether used in the vertical or horizontal orientation. The high-slope passive network minimizes band overlap.

The enclosure is constructed of 15 mm multi-ply high quality plywood and finished in a durable black paint coating. The trapezoid enclosure is fitted with dual Neutrik NL4MP connector for loop thru connection, fifteen M10 threaded suspension points, four M10 screws for Karaoke bracket mounting, a 35 mm pole mount. It utilizes a 16 gauge protective screen backed steel grille to provide driver protection with a very professional appearance.



Specifications:

System:

System Type:	10", 2-way, bass-reflex
Frequency Range (-10 dB) ¹ :	72 Hz - 20 KHz
Frequency Response (±3 dB) ¹ :	90 Hz - 20 KHz
System Sensitivity (1w @ 1m) ¹ :	95 dB
Nominal Impedance:	8 ohms
Maximum SPL:	122 dB (128 dB peak)
Power Rating ² :	300 W/600 W/1200 W
(Continuous/Program/Peak)	
Coverage Pattern:	80° x 70° (H x V)

Physical:

Dimensions (H x W x D):	524 mm x 300 mm x 340 mm 20.6 in x 11.8 in x 13.4 in
Net Weight:	11.9 Kg (26.2 lbs)
LF Driver:	1 x JBL 261H
HF Driver:	1 x JBL 2408H-1
Input Connectors:	2 x Neutrik® Speakon® NL4MP
Enclosure Construction:	Trapezoid, 15 mm, plywood


¹ Full space (4π) conditions

² IEC pink noise with 6 dB crest factor, in frequency range for 2 hours


JBL continually engages in research related to product improvement. Some materials, production methods and design refinements are introduced into existing products without notice as a routine expression of that philosophy. For this reason, any current JBL product may differ in some respect from its published description, but will always equal or exceed the original design specifications unless otherwise stated.

► KP6010 10 Inch 2-Way Full Range Loudspeaker System

Frequency Response and Impedance:




Beamwidth:



Dimensions:

Dimensions in mm (inch)



JBL Professional
8500 Balboa Boulevard, P.O. Box 2200
Northridge, California 91329 U.S.A.

© Copyright 2013 JBL Professional
www.jblpro.com

SSKP6010
SZ
10/13