



### Description

AM 2160 is a mixer-amplifiers with 4 mic-line audio inputs on removable connectors (the first input also has an XLR socket) and 2 aux inputs for music sources (e.g. CD players, tuners, etc.). 160 W nominal output power available either for low impedance loudspeakers or 100 – 70 V constant voltage line.

#### **Features**

- > Full digital technology Mixer Amplifier 160 W RMS
- $\rightarrow$  100 V 70 V and 4 Ohm outputs
- > 4 universal inputs with phantom facility on screw terminal connections
- > Presence Control and per-channel High-Pass filters
- > XLR connector on input 1
- > RJ45 connectors on input 2 and 3 for connection to BM3001 microphone
- > Configurable Priority settings, VOX facility on input 1
- > Aux inputs with volume and tone controls
- > Music On Hold and PRE outputs

## Part Number

12135058 AM 2160


115-230 V

Black

EAN 8024530006396



### Line Art 2D







### **TECHNICAL SPECIFICATIONS**

| Amplifier specifications | Amplifier Class | D |
|--------------------------|-----------------|---|
|                          |                 |   |

Output Power  $1 \times 160 \text{ W} @ 4 \text{ ohm}$  Frequency Response (-3dB)  $50 \text{ Hz} \div 14 \text{ Hz}$  Distortion (THD+N) @ 1 kHz nominal power <0.3 %

# Input section Total number of inputs 8

 Balanced
 7

 Unbalanced
 2

 Mono
 7

 Stereo
 2

 Line inputs
 2

 Line connectors
 RCA

 Mic+Line inputs
 4

Mic+Line connectors

Mic+Line Phantom

VOX

Paging inputs

Paging connectors

RJ45

Paging command

General Purpose Inputs (GPI)

Euroblock, XLR

Euroblock, XLR

Ry45

Cottact

Contact

2

Output sectionSignal output number2Signal output connectorsRCAPower output connectorsEuroblock

Processing Tone controls Yes High-pass filter 150 Hz

**Configuration and control** Configuration DIP switch, Front panel

Priority Yes
Music on hold Yes
Chime tone Yes

Technical Specifications Page 2 of 3



Protections | Cooling Convection

Short circuit Yes
Thermal Yes
DC Yes
Fuses Yes

**Power requirement** Operating voltage 220-240/115 V~ 50/60Hz

Voltage selection Internal Power consumption 350 W

 Standard compliance
 Safety agency
 CE compliant

Physical specificationsCabinet/Case MaterialMetalColorBlackRack mounting19", 2U

SizeHeight88 mm / 3.46 inchesWidth442 mm / 17.4 inches

Depth 230 mm / 9.06 inches Weight 5.4 kg / 11.9 lbs

Technical Specifications Page 3 of 3